




Technical Data Sheet

PN# 200151011034

Shieldex® Conductive Twisted Yarn Silver Plated Nylon 66 Yarn 110/34 dtex 2-ply

- Purpose: anti-microbial applications for garments, smart textiles, and sewing thread
- Description: 99% pure Silver plated Nylon yarn 275/68 dtex
- Liner Resistance: < 500 Ω /M
- Yield: 36,500 M/Kg
- Tenacity: Average 28 cN/tex
- Elongation: abt. 15%
- Denier: 200/68f (S 600 550 tpm Z)
- Melt Point (F): 492



Package Properties

Core Type: 3 Deg-30 Min Cone 9"
Core Material: Pressed Paper or plastic
Product ID Color: Gray
Package Weight: 0.1 LB Nominal
Package Weight Control: +/- .1 lb. within single case

Cross section views of nylon fiber showing silver deposits



Accreditations:

RoHS: Compliant
Reach: Compliant
Acc. ISO 9001:2000



A Family Owned Small Business

VTT/Shieldex Trading USA
4502 Rt-31 Palmyra, NY, 14522

Phone: 315-597-1674
Fax: 315-597-6687
Email: whoge@rochester.rr.com
Www.shieldextrading.net

Statex Productions & Vertriebs GmbH
Kleiner Ort 11 28357 Bremen Germany
Tel: +49 421 275047/8, Fax: +49 421 273643
info@statex.de


© 2010 VTT
Rev 1.20.12