



Technical Data Sheet

PN# 700000300595

Shieldex® Conductive Spun Yarn

5% Silver Plated Nylon/95% Cotton Ne 24/1 or Nm 40/1

- Purpose: anti-microbial applications for knitting or weaving
- Description: 99% pure Silver plated Nylon staple fibers spun with high quality cotton
- Yield: 37,000 M/100g +/- 5%
- Elongation: abt. 3%
- Yarn count: 24/1 Ne (dtex 246) 40/1 Nm



Package Properties

Core Type: 3 Deg-30 Min Cone 9"


Core Material: Pressed Paper or plastic

Product ID Color: Gray

Package Weight: 2.5 LB Nominal

Package Weight Control: +/- .1 lb. within single case

Cross section views of nylon fiber showing silver deposits



Accreditations:

RoHS: Compliant

Reach: Compliant

Acc. ISO 9001:2000



A Family Owned Small Business

VTT/Shieldex Trading USA
4502 Rt-31 Palmyra, NY, 14522

Phone: 315-597-1674

Fax: 315-597-6687

Email: whoge@rochester.rr.com

www.shieldextrading.net

Statex Productions & Vertriebs GmbH
Kleiner Ort 11 28357 Bremen Germany
Tel: +49 421 275047/8, Fax: +49 421 273643
info@statex.de


© 2010 VTT
Rev 1.20.12